



## 3-4 Years Stable PDH Catalyst With 0.63 Kg/M3 Catalyst Loading For Petrochemical Industry

Our Product Introduction

for more products please visit us on [jyalumcatalyst.com](http://jyalumcatalyst.com)

### Basic Information

- Place of Origin: CHINA
- Brand Name: PDH catalyst
- Model Number: KMP-100



### Product Specification

- Shape: Pellet
- Material: Platinum
- Size: 1.6 Mm
- Product Type: Catalyst
- Operating Temperature: 550-650°C
- Bulk Density: 0.62 G/cm3
- Catalyst Loading: 0.63 Kg/m3
- Lifetime: 3-4 Years
- Highlight: **stable pdh catalyst, stable platinum catalyst, petrochemical pdh catalyst**

## Product Description

### Product Description:

The PDH Catalyst boasts a size of 1.6 mm and a pore size of 20 nm, making it ideal for use in moving bed applications. Its advanced design allows it to operate at temperatures ranging from 550-650°C, ensuring optimal performance in even the most demanding environments.

Whether you're looking to improve the productivity of your oil column or enhance the efficiency of your oil ammonia column, the PDH Catalyst is the perfect solution. Its advanced design and high-quality construction make it the catalyst of choice for companies in a wide range of industries, from chemical manufacturing to oil and gas.

In addition to its impressive performance capabilities, the PDH Catalyst is also incredibly easy to use. Simply add it to your oil or oil ammonia column and let it do the rest. Its innovative design ensures that it will work seamlessly with your existing equipment, making it a hassle-free solution for companies of all sizes.

If you're looking for a high-quality catalyst that can help you achieve your goals and take your business to the next level, look no further than the PDH Catalyst. With its advanced design, superior performance, and ease of use, it's the perfect choice for companies in a wide range of industries.

### Technical Parameters:

Product Type	Catalyst
Shape	Pellet
Pore Size	20 Nm
Bulk Density	0.62 G/cm3
Operating Temperature	550-650°C
Application	Petrochemical Industry (moving bed, oil column)
Material	Platinum
Size	1.6 Mm
Catalyst Loading	0.63 Kg/m3
Surface Area	100 M2/g

### Support and Services:

Our PDH Catalyst product comes with comprehensive technical support and services to ensure optimal performance and efficiency. Our team of experienced technical experts is available to assist with installation, commissioning, troubleshooting, and maintenance of the PDH Catalyst product. We offer on-site training and support to help you get the most out of your investment. In addition, we also provide regular software updates and upgrades to ensure that your PDH Catalyst product is always up-to-date with the latest technology. Contact us for more information on our product technical support and services.

### Packing and Shipping:

Product Packaging:

The PDH Catalyst product will be carefully packaged in a sturdy box to ensure that it is not damaged during shipping. The product will be wrapped in bubble wrap and placed securely in the center of the box. Additionally, the box will be labeled with the necessary shipping information, including the recipient's name and address.

Shipping:

We offer free shipping for the PDH Catalyst product within the United States. For international orders, shipping fees will apply. Once the order is confirmed, we will ship the product within 2-3 business days. The estimated delivery time for domestic orders is 5-7 business days. For international orders, the estimated delivery time is 10-14 business days. Customers will receive a tracking number via email once the product has been shipped.



Qingdao Junyao Catalyst New Material Technology Co., Ltd.

+8618254266810

[jycat@qdjunyao.com.cn](mailto:jycat@qdjunyao.com.cn)

[jyalumcatalyst.com](http://jyalumcatalyst.com)